

SafeTacVRD[®]
Welding & Safety Products

SAFETAC EXTERNAL PORTABLE GPSS2 (250 AMP)



KEY FEATURES

- Input volts 20 to 130 Volts AC/DC + reverse polarity DC
- Rated at 250 Amps @ 100% duty cycle
- 1 Meter x 50mm² input & output cables
- Constructed from 304 S/S
- "O-Ring" led seals
- "O" Ring sealed chromed brass cable glands
- Turn off resistance 20 to 150 Ohms / Turn greater than 200 Ohms
- VRD turn on time .3 seconds programmable to 5 seconds
- Reduced output volts approximately 12 VDC
- Warranty 1 Year RTB
- N.A.T.A. tested
- Can be permanently mounted using 8mm tamperproof bolts
- No effect on welding machines duty cycle or weld characteristics
- Built in fail alarm test (Visual , Audible upon request)

PRODUCT DIMENTIONS

Height: 105mm width: 120mm length: 220mm weight: 6.2 Kgs
Shipping dimensions: 290mm x 420mm x 180mm x 7.0 Kgs

VRD

WELDING & SAFETY PRODUCTS

HEAD OFFICE / FACTORY
UNIT 1 / 30 BUSHLAND RIDGE
BIBRA LAKE, 6163
WESTERN AUSTRALIA

WHO WE ARE
SAFETAC WELDING PRODUCTS
PTY LTD
ABN 87 095 707 396

TELEPHONE
BUSINESS: +618 9494 1205
FAX: +618 94187465
AFTER HOURS: 0408 477 120

EMAIL
SALES@VRD.COM.AU



VIEW THIS PRODUCT

Scan this QR code to
view the product online

WWW.VRD.COM.AU